



Zenith Blackout Fabric Product Specifications

©2016

Benefits: A picture of refined elegance, Zenith Blackout fabric layers a subtle, textured pattern over a soft, luxurious backing for total light blockage.

Specifications

Category	Blackout fabric	Composition	100% polyester with acrylic foamed backing
Openness Factor	0%; opaque		
UV Blockage	100%	Weight	12.53 oz/yd ² (425 s/m ²)
Thickness	0.029" (0.74 mm)	Width	118" (300 cm)

Fire Classification NFPA 701-2004 TM#1 (small scale)
California U.S. Title 19 (small scale)

Anti-Microbial Properties: ASTM E2180
ASTM G21

Certifications: GreenGuard Gold
Melanoma International Foundation Seal of Approval

Environmental Benefits: PVC-free
RoHS compliant- Lead Free

Care & Cleaning: Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.

For complete technical information, current test results, performance specifications and larger samples, contact the Insolroll, Inc.

Insolroll Window Shading Systems | 637 S. Pierce Ave. | Louisville, CO | 80027
tel 800.447.5534 | www.insolroll.com | info@insolroll.com